

## ENTERPRISE S-SERIES

# MP-SA50 HIGHLY CUSTOMIZABLE AND HIGH- ENDURANCE SATA SSD FOR YOUR ENTERPRISE

MiPhi MP-SA50 SSD is a highly customizable SATA SSD solution line that scales to 15.36TB (MP-SA50V) and up to 3 DWPD (MP-SA50E) giving you ample options for your diverse application and cold storage needs.

KEY FEATURES	
Interface	SATA III
NAND Flash	3D TLC
DWPD	0.4, 1, 3
UBER	<1 sector per 10 bits
Operating Temperature	0°C - 70°C
Non-Operating Temperature	-40°C - 85°C
MTBF (million years)	2



## PRODUCT FEATURES

### Reliability

The MP-SA50 Series SSD leverages MiPhi's 4th generation LDPC ECC engine which can correct up to 160 bits for each 2048 byte block through the hard decoder, and up to 400 bits for each 2048 byte block using the soft decoder. This ensures customers' data is protected throughout the life of the SSD.

### Excellent Scalability

The MP-SA50 supports up to 8 NAND flash data transmitting channels with up to 32 Chip Enable (CE) counts running on mainstream NAND flash interfaces in ONFI and Toggle and allowing capacity scaling from 240 GB up to 15.36 TB.

### SATA Compatibility

The MP-SA50 Series SSD is plug wise compatible with SATA backplanes, making it easy to install in existing backplanes as new storage, or to replace HDDs with a performance upgrade.

### End-to-End Data Path Protection

From the moment data enters the MP-SA50 Series SSD, a parity bit is generated that follows each byte from the interface to the NAND storage area ensuring user data has the maximum protection in integrity.

# MP-SA50P Specifications

2.5"						
	Capacity	480GB	960GB	1920GB	3840GB	7680GB
Performance	Seq Read	530 MB/s	530 MB/s	530 MB/s	530 MB/s	530 MB/s
	Seq Write	360 MB/s	500 MB/s	500 MB/s	500 MB/s	500 MB/s
	Random Read	92K IOPS	98K IOPS	98K IOPS	98K IOPS	97K IOPS
	Random Write	20K IOPS	33K IOPS	40K IOPS	30K IOPS	23K IOPS
Power Consumption	Max	2.6 W	3.0 W	3.1 W	3.3 W	3.7 W
	Idle	1.3 W	1.3 W	1.4 W	1.5 W	1.7 W
Latency	Read Latency	140 us	120 us	120 us	130 us	160 us
	Write Latency	50 us	40 us	30 us	35 us	45 us

KEY FEATURES	
Enterprise Features Support List: <ul style="list-style-type: none"><li>• Namespace</li><li>• Dual port</li><li>• Reservation</li><li>• Metadata protection</li><li>• Powerloss protection</li><li>• Hardware AES-XTS 256-bit encryption</li><li>• Support SMBbus</li></ul>	Compliance Support List <ul style="list-style-type: none"><li>• Management Interface</li><li>• Rev 1.1 TCG Opal 2.0(6)</li><li>• Sanitize(6)</li></ul>

(1) 1 GB = 1,000,000,000 bytes.  
(2) Sequential Performance is based on FIO on Linux, 128K, with QD=32, 1 worker, and test drive set as secondary.  
(3) Random Performance is based on FIO on Linux, 4K data size, QD=32, 1 worker, 4K aligned.  
(4) Power consumption is measured during the sequential read/write and random read/write operations performed by iometer with the conditions described in (2)(3).  
(5) The results of DWPD are obtained in compliance with JESD219A Standards.



The data within this specification is subject to change by MiPhi without notice. Performance numbers may vary based on system configuration and testing conditions. Copyright © 2025 MiPhi Semiconductors Private Limited. All rights reserved.

# MP-SA50E Specifications

2.5"					
	Capacity	480GB	960GB	1920GB	3840GB
Performance	Seq Read	500 MB/s	530 MB/s	530 MB/s	530 MB/s
	Seq Write	440 MB/s	500 MB/s	500 MB/s	500 MB/s
	Random Read	95K IOPS	98K IOPS	98K IOPS	98K IOPS
	Random Write	40K IOPS	67K IOPS	77K IOPS	68K IOPS
Power Consumption	Max	2.8 W	3.0 W	3.1 W	3.5 W
	Idle	1.3 W	1.4 W	1.5 W	1.7 W
Latency	Read Latency	130 us	125 us	130 us	125 us
	Write Latency	30 us	30 us	30 us	30 us

KEY FEATURES	
Enterprise Features Support List: <ul style="list-style-type: none"><li>• Namespace</li><li>• Dual port</li><li>• Reservation</li><li>• Metadata protection</li><li>• Powerloss protection</li><li>• Hardware AES-XTS 256-bit encryption</li><li>• Support SMBbus</li></ul>	Compliance Support List <ul style="list-style-type: none"><li>• Management Interface</li><li>• Rev 1.1 TCG Opal 2.0(6)</li><li>• Sanitize(6)</li></ul>

(1) 1 GB = 1,000,000,000 bytes.  
(2) Sequential Performance is based on FIO on Linux, 128K, with QD=32, 1 worker, and test drive set as secondary.  
(3) Random Performance is based on FIO on Linux, 4K data size, QD=32, 1 worker, 4K aligned.  
(4) Power consumption is measured during the sequential read/write and random read/write operations performed by iometer with the conditions described in (2)(3).  
(5) The results of DWPD are obtained in compliance with JESD219A Standards.



The data within this specification is subject to change by MiPhi without notice. Performance numbers may vary based on system configuration and testing conditions. Copyright © 2025 MiPhi Semiconductors Private Limited. All rights reserved.

# MP-SA50V Specifications

2.5"					
	Capacity	1920GB	3840GB	7680GB	15360GB
Performance	Seq Read	530 MB/s	530 MB/s	530 MB/s	530 MB/s
	Seq Write	500 MB/s	500 MB/s	500 MB/s	500 MB/s
	Random Read	94K IOPS	97K IOPS	97K IOPS	94K IOPS
	Random Write	13K IOPS	20K IOPS	14K IOPS	10K IOPS
Power Consumption	Max	3.3 W	3.6 W	3.9 W	4.2 W
	Idle	1.4 W	1.5 W	1.9 W	1.9 W
Latency	Read Latency	135 us	130 us	140 us	165 us
	Write Latency	55 us	40 us	55 us	65 us

KEY FEATURES	
Enterprise Features Support List: <ul style="list-style-type: none"><li>• Namespace</li><li>• Dual port</li><li>• Reservation</li><li>• Metadata protection</li><li>• Powerloss protection</li><li>• Hardware AES-XTS 256-bit encryption</li><li>• Support SMBbus</li></ul>	Compliance Support List <ul style="list-style-type: none"><li>• Management Interface</li><li>• Rev 1.1 TCG Opal 2.0(6)</li><li>• Sanitize(6)</li></ul>

(1) 1 GB = 1,000,000,000 bytes.  
(2) Sequential Performance is based on FIO on Linux, 128K, with QD=32, 1 worker, and test drive set as secondary.  
(3) Random Performance is based on FIO on Linux, 4K data size, QD=32, 1 worker, 4K aligned.  
(4) Power consumption is measured during the sequential read/write and random read/write operations performed by iometer with the conditions described in (2)(3).  
(5) The results of DWPD are obtained in compliance with JESD219A Standards.



The data within this specification is subject to change by MiPhi without notice. Performance numbers may vary based on system configuration and testing conditions. Copyright © 2025 MiPhi Semiconductors Private Limited. All rights reserved.