



ENTERPRISE X-SERIES

MP-SA50 Highly Customizable and High-Endurance SATA SSD for your Enterprise

Miphi SA50 SSD is a highly customizable SATA SSD solution line that scales to 15.36TB (SA50V) and up to 3 DWPD (SA50E) giving you ample options for your diverse application and cold storage needs.



Product Features

Reliability

The SA50 Series SSD leverages Miphi's 4th generation LDPC ECC engine which can correct up to 160 bits for each 2048 byte block through the hard decoder, and up to 400 bits for each 2048 byte block using the soft decoder. This ensures customers' data is protected throughout the life of the SSD.

Excellent Scalability

The SA50 supports up to 8 NAND flash data transmitting channels with up to 32 Chip Enable (CE) counts running on mainstream NAND flash interfaces in ONFI and Toggle and allowing capacity scaling from 240 GB up to 15.36 TB.

SATA Compatibility

The SA50 Series SSD is plug wise compatible with SATA backplanes, making it easy to install in existing backplanes as new storage, or to replace HDDs with a performance upgrade.

End-to-End Data Path Protection

From the moment data enters the SA50 Series SSD, a parity bit is generated that follows each byte from the interface to the NAND storage area ensuring user data has the maximum protection in integrity.

Solutions MP-SA50E

2.5"					
Capacity ⁽¹⁾		480GB	960GB	1920GB	3840GB
Performance ^(2,3) (Est.)	Sequential Read	500 MB/s	530 MB/s	530 MB/s	530 MB/s
	Sequential Write	440 MB/s	500 MB/s	500 MB/s	500 MB/s
	4K Random Read	95K IOPS	98K IOPS	98K IOPS	98K IOPS
	4K Random Write	40K IOPS	67K IOPS	77K IOPS	68K IOPS
Power Consumption ⁽⁴⁾ (Est.)	Max	2.9 W	3.2 W	3.3 W 1.4	3.5 W
	Idle	1.3 W	1.4 W	W 130 us	1.6 W
Latency (Est.)	4K Random Read	130 us	125 us	30 us	125 us
	4K Random Write	30 us	30 us	30 us	30 us
Features					
Interface			SATA III		
NAND Flash			3D TLC		
DWPD ⁽⁵⁾			3		
UBER			1 in 10 ¹⁷		
Operating Temperature			0°C - 70°C		
Non-OperatingTemperature			-40°C - 85°C		
Key Features					
<ul style="list-style-type: none">LDPCPower Loss Data ProtectionEnd-to-End Data Protection					
Part Number					
Non-SED		MPSA50E480G-N	MPSA50E960G-N	MPSA50E1920G-N	MPSA50E3840G-N
SED		MPSA50E480G-S	MPSA50E960G-S	MPSA50E1920G-S	MPSA50E3840G-S

(1) 1 GB = 1,000,000,000 bytes.

(2) Sequential Performance is based on FIO on Linux, 128K, with QD=32, 1 worker, and test drive set as secondary.

(3) Random Performance is based on FIO on Linux, 4K data size, QD=32, 1 worker, 4K aligned.

(4) Power consumption is measured during the sequential read/write and random read/write operations performed by iometer with the conditions described in (2)(3).

(5) The results of DWPD are obtained in compliance with JESD219A Standards.